MARCO idoc® SYSTEM REQUIREMENTS

HARDWARE & SOFTWARE SPECIFICATIONS: CAMERA SPECIFICATIONS:

05 Windows XP 32 bit/64 bit (All Editions) SP2/SP3 Windows Vista 32 bit/64 bit (All Editions)

Windows 7 32 bit/64 bit (All Editions) SP1

Intel Core i3-213Ø CPU @ 3.40GHz CPU

RAM 4GB

HD 200GB or more

Drive CD-RW

Video Card Any video card which has enough capacity to show high quality images. (Consult your IT professional.)

I/F Desktop IEEE 1394A (Firewire) PCI board is required to be

installed, 1 RS232-C Serial Port (or Serial to USB

adapter), 4 or more open USB 2.0 ports at the rear of the computer case.

Externally powered IEEE 1394A (Firewire) card I/F Laptop for the specific laptop auxiliary card slot.

These are absolute minimum requirements. Exceeding these requirements will enhance performance.

Image Device 1/2" Type progressive scan SONY IT CCD

Effective

Picture Elements Up to 1388 x 1038 pixel

Resolution Depth 8 bit

Color Modes Raw8 (Mono8), YUV4:2.2, YUV4:1:1

Digital Interface IEEE1394; DCAM V1.30 **Transfer Rate** 100, 200, 400 Mb/s

Frame Rate 15MHz at full resolution

(1388 x 1038)

Power Requirements DC 8V-36V via IEEE1394 Cable

Power Consumption Less than 3 Watt(@12 VDC)

Beamsplitter ratio for adaptor is 70% camera and 30% examiner.