



UDR-800

DIGITALIZED REFRACTOR



Brilliantly Conceived & Beautifully Crafted

UNICOS is A Health Care Business Venture Comany.

UDR 800

DIGITAL REFRACTOR FEATURES

Eco-friendly & Design using antibacterial material

| | | | |
|--------------------------|-------------------------------|------------------------------------|--------------------------------|
| Reduced Body Size | Faster Restarting Time | Faster Speed of Lens Change | Reduced Operating Noise |
|--------------------------|-------------------------------|------------------------------------|--------------------------------|

8.0 Inch Full-Colored Touch LCD Panel

- It could serve clear distinct UI so that it may serve high resolution graphic.
- Realize UI with various images and distinguish the condition of Operation Panel and data by serving various colors. (Locking system function, Prismoff, Auxoff function, External data representation and Touch masking function, etc.)

Minimized number of buttons



Short cut key button for often used functions

- Operating test data through jog dial. (SPH, CYL, AXIS, ADD, VA, Prism, etc.)
- Menu selection through jog dial.
- Additional functions and data value selection through jog dial.
- Shortcut key button function.

- 26-Button and simply touch to operate easily.

Perfect Interface with Ref/Keratometer, Chart Pro ector, LCD Projector and Lensmeter

- It could serve receiving Data from URK-700 & URK-800F and saving DB.
- It could be connected with A, B, C and D type of ACP-700 including ULC-900. (UDR-700 could be connected only with A type of ACP-700.)

Monocular PD measurement

Worldwide Various Chart Support

LCD Monitor Tilting function and Screen reversal function

Embedded printer

Help and Real-time Guide function


It could serve upgrading program and A/S functions by USB port

Simple GUI for User Convenience (Various Vision Test Function Offer)


INTRODUCTION




SCREEN 1




SCREEN 2




SCREEN 3




SCREEN 4



SCREEN 5



SCREEN 6



Networking System

Efficient data transmission among a series of UNICOS Brands.

Measuring Range

| | |
|------------------|---|
| Spherical Lens | -29.00 ~ +26.75D (For general test) -19.00 ~ +16.75D (For cross cylinder & Prism test) (Step 0.12D / 0.25D / 0.5D / 1D / 2D / 3D) |
| Cylinder Lens | 0.00 ~ 8.75D (Step 0.25D / 0.5D / 1D / 2D / 3D) |
| Cylinder Axis | 0 ~ 180° (Step 1 / 5 / 15 / 30 / 45°) |
| Pupil Distance | Far 48 ~ 80 mm (Step 0.5 / 1.0 mm) Near 45 ~ 75 mm (Step 0.5 / 1.0 mm) |
| Working Distance | 35 ~ 70 cm (Step 5 cm) |
| Rotary Prism | 0 ~ 20 Δ (Step 0.1 Δ / 0.2 Δ / 0.5 Δ / 1 Δ / 2 Δ) |
| Cross Cylinder | Jackson Cross Cylinder ±0.25D Jackson Cross Cylinder ±0.50D Dual Cross Cylind |
| Retinoscopy Lens | +1.5D, +2.0D (Test Distance 67cm, 50cm) |

Specifications

| | |
|-------------------|---------------------------------|
| Body | 362(W) X 82(D) X 229(H), 3.5Kg |
| Controller | 215(W) X 230(D) X 226(H), 1.5Kg |
| Junction Box | 266(W) X 60(D) X 239(H), 1.0Kg |
| Power Supply | AC 100 ~ 240V, 50/60Hz |
| Power Consumption | 60 ~ 95VA |

Auxiliar Lens

| | |
|---------------------------|---|
| Open/ Close Lens | |
| Pin Hole Lens | Φ 1mm |
| Moddox Rod | Right Eye (Horizontal Red), Left Eye (Vertical Red) |
| Red / Green Filter | Right Eye (Red), Left Eye (Green) |
| Polarized Light Filter | Right Eye (135°, 45°), Left eye (45°, 135°) |
| Separating Prism | Right Eye (6ΔBU) Left eye (10ΔBI can be added to 0~5Δ) |
| PD Test Lens | |
| Fixed Cross Cylinder Lens | Jackson Cross Cylinder ±0.05D, Axis fixation 90° |
| Vision Degrees | 32° |

Designs and details can be changed without prior notice for its improvements.



MERCOFrames OPTICAL CORP.

© 5555 NW 74 AVE. Miami, FL 33166 [/mercoframes](https://www.facebook.com/mercoframes)

✉ sales@mercoframes.net www.mercoframes.com

☎ 305-882-0120 Whatsapp www.mercoframesusa.com