

### **Specification**

Charts	42 Charts	
Distance of projection	2.5 - 8 m (8 m distance projection screen is optional)	
Chart magnification	30x (When projected at 5 m distance)	
Lamp	LED Lamp	
<b>Chart Rotation Speed</b>	Average 0.3sec	
Power Save	11 minutes (after last signal)	
Tilt angle	± 20 degrees	
Resolution	50 lines / mm	
Program	2 programs with a maximum of 40 charts each	
Power Supply	100 - 240V~, 50/60Hz	
Power consumption	25 - 35VA	
Dimension	Body (Stand except)	200(W) × 290(D) × 172(H) mm
	Body (Stand included)	200(W) × 290(D) × 235(H) mm
	Remote Controller	64(W) × 196(D) × 20(H) mm
Weight	Stand included	3.58 kg
	Remote controller	160 g (Battery included)
Standard Accessories	<ul> <li>Remote Controller</li> <li>Screen, Dust cover</li> <li>Power Cable</li> <li>Stand, T wrench</li> <li>Fuse, Battery</li> </ul>	
Optional Accessories	· Red / Green glasses · Polarization glasses	

<sup>\*</sup>Designs and details can be changed without prior notice its impprovements.

Refined design and Compact size

# PACP-8000

AUTO CHART PROJECTOR








PACP-8000 provides optometry with the greater convenience using the refined design, a compact size, and diversified charts.


# PACP-8000 AUTO CHART PROJECTOR








— Type C



— Type R



- Type D





### **Eyesight measurement using diversified charts**

Diversified charts (4 types of A/C/D/R) per country are retained including binocular balance, aniseikonia, stereopsis, binocular vision test chart



#### Cost saving through adoption of LED light source

Maintenance & repair costs can be saved through adoption of LED light source having a semi-permanent service life





#### **Bright & clear chart display**

Brighter & clear chart display is provided by adoption of white LED





#### Refined design

Optometry room is made to stand out by the refined design embodying an eyeball.



#### **Compact size**

A roomy optometry space is provided using a more compact size

Size: 25% Reduction comparing with PACP-7000 Weight: 25% lighter than PACP-7000



#### **Convenient focus adjustment**

Convenient focus adjustment is enabled by a rotary aperture.