AUTOLENSMETER TL-100

SMALL BUT EFFICIENT

DELIGHT IN SIGHT

Quick and easy measurement. High value. Low cost.

AUTO LENSMETER TL-100 C READING

Contact lens mode

Auto hold function

0

- More performance for less money
- Prismatic lens measurement
- Automated detection and measurement of progressive lenses



Allan Bas

THE TOMEY AUTOLENSMETER TL-100

\mathcal{A}

QUALITY IN DETAIL

The Tomey AutoLensmeter **TL-100**: quick and easy operation. Small in size but huge in functionality. You can check all relevant lenses with our **TL-100**. The unit allows measuring of all standard lenses, high-index lenses, bifocal and progressive lenses including prismatic power. You may adjust the ABBE number according to your needs. The unit ensures easy measurement of all contact lenses in dry mode. The **TL-100** has been designed with a minimal footprint, occupying little valuable space in your refraction room or laboratory. With its outstanding performance, the **TL-100** will be a high-value, low-cost addition to your practice.





SPECIFICATIONS	
MEASUREMENT RANGES	
Sphere power	+/- 25 D
Cylinder power	+/- 9.99 D
Axis	0 to 180°
ADD	0 to 9.99 D
Prism	0 to 9.99 Δ
MEASUREMENT INCREMENTS	
Diopter	0.01 / 0.12 / 0.25 D
Prism	0.01 / 0.12 / 0.25 ∆
MEASUREMENT MODES	
Cylinder	+/±/-
Prism	Rectangular coordinates /
	polar coordinates
Lens modes	Standard / high index /
	bifocal / progressive lenses
Contact lens mode	Yes
MEASUREMENT PARAMETERS	
Measurement time	0.035 sec.
Wave length	660 nm
Sensor diameter / beam diameter	3 mm / 10 mm
Lens blanks	20 to 100 mm
Setting of ABBE number	30 to 65
DATA CONTROL	
Display	LCD DOT (monochrome),
	<i>Size: 4.0"</i>
INCHES	
Memory	Single
Switch button	Mechanical
MARKING	
Unit	Plastic
Cartridge	White
DIMENSIONS & ELECTRIC REQUIREM	
Dimensions WDH	200 x 260 x 436 mm
Weight	Approx. 5.0 kg
Input	AC 100 V to 240 V
Frequency	50/60 Hz
Power consumption	Less than 40 VA



MERCOFRAMES OPTICAL CORP 5555 Nw 74 Ave. Miami. Fl. 33166 Tel. 305-882-0120 ale@mercoframes.com