PT100 Quick Reference Sheet

Display and Control Panel



Function Icons

| DEMO | Press to allow patient to feel demonstration air puff |
|-------------|--|
| OVERRIDE | Permits quicker measurement of difficult patients |
| SETUP | Enables access to the setup menu of the instrument |
| LEFT/RIGHT | Press to select the patient's right or left eye |
| PRINT | Transmits measurement data to printer or IR COM device |
| CLEAR | Erases current measurement data from display screen |
| Setup Icons | |
| up | Setup menu only. Moves up through menu options. |
| down | Setup menu only. Moves down through menu options. |

Holding the PT100

Setup menu only. Activates the new setting.



- Place one hand on the handle and the other between the top-front of the instrument and the patient's brow.
- Look through the eyepiece and position the black circle over the pupil.
- Slowly move the PT100 towards the eye until the alignment system activates.

13850-104 Rev. A



select

MERCOFRAMES OPTICAL CORP.


© 5555 NW 74 AVE. Miami, FL 33166 ⊠ sales@mercoframes.net ⊗ 305-882-0120 ^{Whatsapp} ⇒ www.mercoframesusa.com

PT100 Quick Reference Sheet

Alignment System

- Proper alignment requires slow, steady movements
- First, use the distance indicators to attain correct distance from the eye
- Next, move the instrument to align the crosshair over the centering target
- Once aligned, the PT100 will automatically take an IOP measurement

NOTE: The working distance is approximately 12mm (1/2") from the eye





13850-104 Rev. A



MERCOFRAMES OPTICAL CORP.

© 5555 NW 74 AVE. Miami, FL 33166 I mercoframes.net Sales@mercoframes.net Sales@mercoframes.com Sales@mercoframes.com