

SLIT LAMP MICROSCOPE

ASL-1300

- Two-Step magnifications: 10x , 16x.
- All the optical lenses are moisture-proof, and mildew-proof anti-reflected treated.
- Excellent optical performances.
- Convenient and compact.



SPECIFICATIONS

Microscope Type	Converging Stereoscopic Microscope
Objective Magnification	Two Steps Magnifications
EyePiece	10x
Magnifications (Field of view)	10x(ϕ 18mm) 16(ϕ 11.25mm)
Puil Distance	55mm ~ 82mm
Diopter Adjustment	\pm 6D
Slit width	0mm ~ 9mm adjustable (slit round when the slit width is 9mm)
Slit Height	1mm ~ 8mm adjustable
Slit Angle	0° ~ 180° ajustable
Slit Inclination	5°, 10°, 15°, 20° four steps
Filers	Heat Absorption, Grey, Redfree, Cobalt blue
Diameter of Light Spot	ϕ 9mm, ϕ 8mm, ϕ 5mm, ϕ 3mm, ϕ 2mm, ϕ 1mm, ϕ 0.2mm
Power Supply	AC110V/220V \pm 10%, 50Hz/60Hz
Packing Volume	670mm x 620mm x 490mm
Total Weight	23Kg
Optional Accesories	R-type, T-type applanation tonometer, measuring EyePiece, Trihedron Lens, Gonioscope, Funduscope, Asperic Lens



 mercoframes.com