

# AUTO-LENSMETER CF-2000 / CF-3000

AUTOMATED LENSMETER

## DELIGHT IN SIGHT

Sophisticated, intuitive.



- Touch screen
- Modern progressive mode (FAR, MID, NEAR)
- Very precise marking unit (metal)
- Refractive index
- PD measurement / quality check (CF-3000)
- UV-measurement (CF-3000)


**TMIC**  
a TOMEY company

# THE TOMHEY CF-2000 / CF-3000 AUTO-LENSMETER




## QUALITY IN DETAIL


The Tomhey CF-2000 / CF-3000 are very easy to operate with the 5.7" touch screen. Icons will guide you through the whole menu and guarantee fast and intuitive operations. The sophisticated auto-measurement function and the automated detection of progressive lenses are just two of many advanced features.



The CF-2000 / CF-3000 have a refractive index calculation programme included. You just enter the curvature and the index will be calculated automatically.



The system detects and measures automatically all progressive lenses. Also modern multi-focal lenses may be measured in FAR, MID and NEAR areas.



QC check mode – Quality Control: The CF-3000 visualises the quality of the centration in accordance to the laboratory parameters.

## SPECIFICATIONS CF-2000 / CF-3000

<b>Measurement range</b>	
<b>Sphere (SPH)</b>	±25 D
<b>Cylinder (CYL)</b>	±10 D
<b>Axis (AXIS)</b>	0 to 180°
<b>ADD</b>	-2 to 10 D
<b>Prism</b>	0 to 10 Δ
<b>Measurement increment</b>	
<b>Dioptre</b>	0.01 / 0.12 / 0.25 D
<b>Prism</b>	0.01 / 0.12 / 0.25 Δ
<b>Measurement parameters</b>	
<b>Time</b>	0.035 sec.
<b>Wavelength</b>	660 nm
<b>Beam diameter</b>	Ø 3 mm (CF-2000) Ø 2.5 mm / 5 mm (CF-3000)
<b>Lens diameter</b>	Ø 20 to 100 mm
<b>ABBE number</b>	30 to 65
<b>Ref. index calculation</b>	YES
<b>UV light transmittance</b>	385 nm (CF-3000)
<b>PD measurement</b>	50 to 86 mm (0.5 mm increments) (CF-3000)

<b>Measurement mode</b>	
<b>Cylinder</b>	+ / ± / -
<b>Prism</b>	Rectangular coordinates / polar coordinates / displacement
<b>Data control</b>	
<b>Display</b>	5.7" LCD colour touch panel
<b>Alignment</b>	Cross cursor
<b>Printer</b>	Thermal printer
<b>Memory</b>	99 single measurements
<b>External communication</b>	RS-232C
<b>Marking unit</b>	Metal
<b>Cartridge</b>	White
<b>Dimensions &amp; electrical requirements</b>	
<b>Dimensions WDH</b>	220 x 260 x 438 mm
<b>Weight</b>	Approx. 7 kg
<b>Input</b>	AC 100 to 240 V
<b>Frequency</b>	50/60 Hz
<b>Power consumption</b>	Less than 40 VA (CF-2000) 35 to 50 VA (CF-3000)

2013/09 - subject to change without notice



# MERCOFrames OPTICAL CORP

5555 Nw 74 Ave. Miami, Fl. 33166

Tel. 305-882-0120

ale@mercoframes.com